

GPT.05.153.100

Revision: 00



SUZUKI DR 650

## Alu-Rack Montagehinweise

Alle vom Motorrad gelösten Schrauben sind gemäß Herstellerangaben wieder zu montieren, oder mit von SW-MOTECH gelieferten Schrauben zu ersetzen. Falls nicht anderweitig definiert, diese Schrauben nach Tabelle anziehen.

|     |        |
|-----|--------|
| M6  | 9,6 Nm |
| M8  | 23 Nm  |
| M10 | 46 Nm  |

Gegebenenfalls Schrauben mit flüssiger Schraubensicherung einkleben.

Prüfen Sie nach 50 km alle Verbindungen auf festen Sitz.

Max. Zuladung 12 Kg.

Ist das Zuladungsgewicht des Fahrzeuges durch den Hersteller limitiert, gelten diese Grenzwerte.

SW-MOTECH GmbH & Co. KG  
Bahnhofstrasse 44d  
35282 Rauschenberg  
-Germany-

Tel.: ++ 49 (0) 6425 816 800

Fax: ++ 49 (0) 6425 816 810

www.sw-motech.com

## Alu-Rack Mounting Instructions

SW-MOTECH products should be installed by a qualified, experienced motorcycle technician. If you are unsure of your ability to properly install a product, please have the product installed by your local motorcycle dealer. SW-MOTECH takes no responsibility for damages caused by improper installation.

All screws, bolts and nuts, including all replacement hardware provided by SW-MOTECH, should be tightened to the torque specified in the OEM maintenance manual for your motorcycle. If no torque specifications are provided in the OEM maintenance manual, the following torques may be used:

|     |        |
|-----|--------|
| M6  | 9,6 Nm |
| M8  | 23 Nm  |
| M10 | 46 Nm  |

All screws, bolts and nuts should be checked after driving the first 50 km to ensure that all are tightened to the proper torque.

Medium strength liquid thread-locker (i.e., "Locktite") should be used to secure all screws, bolts and nuts.

Max. Load On Rear Carrier: 12 Kg (26 lbs) or the motorcycle manufacturer's weight limit, whichever is less.

1

Alu-Rack  
Alu-Rack



schwarz/black

GPT.04.422.001 01

Anzahl/ Pcs. 1

2

Senkkopfschraube  
mit Innensechskant  
Countersunk Screw



schwarz/black

M8 x 25 DIN 7991

Anzahl/ Pcs. 4

3

Mutter mit Bund,  
selbstsichernd  
Lock Nut with Flange



schwarz/black

M8 DIN 6927/b

Anzahl/ Pcs. 4

4

Montagebrücke vorne  
Front Mounting Bridge



GPT.05.153.002 00

Anzahl/ Pcs. 1

5

Innensechskantschraube  
Hexagon Socket Screw



M8 x 45 DIN 912

Anzahl/ Pcs. 2

7

Montagebrücke hinten  
Rear Mounting Bridge



GPT.05.153.003 00

Anzahl/ Pcs. 1

8

Sechskantschraube  
Hexagon Screw



M8 x 35 DIN 933

Anzahl/ Pcs. 2

6

Distanzbuchse  
Spacer



Da:20 Di:8,4 h:4

Anzahl/ Pcs. 2

9

Unterlegscheibe  
Washer



A 8,4 DIN 125

Anzahl/ Pcs. 2

10

Distanzbuchse  
Spacer



Da:20 Di:8,4 h:9

Anzahl/ Pcs. 2

