



FITTING INSTRUCTIONS FOR LP0084BK LICENCE PLATE BRACKET APRILIA RSV4 2009



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away!*

YOU WILL NEED THE FOLLOWING TOOLS TO COMPLETE THIS JOB

Long Phillips screwdriver.
Set of metric allen keys.
Electrical crimping pliers.
Set of spanners.
Long nose pliers

- Remove the rear cowl / pillion seat.
- Disconnect wiring plugs for indicators.
- Undo and remove OEM licence plate bracket (four Phillips screws the nuts can be seen under pillion seat) while supporting tail bracket and feeding wires carefully through holes in under-tray.
- If fitting OEM indicators remove OEM indicators from tail bracket. This is done by removing the lenses, then pulling out the reflector and disconnecting the two wires, pull the wires back through the indicator (please note the plug colour coding and the side to which it relates).
- Fit the two parts of the tail tidy together using the four M6x6mm long button head bolts (suggest using some thread lock or super glue on the threads)
- Fit indicators to new licence plate bracket (either OEM or after market minis - suggest R&G micro indicators, product code RG370).
- Fit new licence plate light to new licence plate bracket and tighten.(note it will be necessary to cut the wire to the OEM license plate light in order to join them to the R&G light with the connectors supplied)
- Fit the smaller supplied heat shrink supplied over wires.

R&G Racing
Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX
Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com



- Feed all wires through the under-tray as original use the larger heat shrink to tidy up all the wires.
- Using the four OEM nuts and bolts (put bolts though from underneath and nuts from top) secure new licence plate bracket.
- Reconnect all wiring and wiring plugs as original. Using wiring clips from kit secure wires to new licence plate bracket.
- Fit licence plate to new licence plate bracket.
- **IMPORTANT: IF FITTING A FULL-SIZE LICENCE PLATE AND PLACING IT FAR DOWN ON THE LICENCE PLATE HANGER, THERE IS A SMALL CHANCE OF THE LICENCE PLATE HITTING THE BACK WHEEL UNDER HEAVY LOAD AND OVER LARGE BUMPS IN THE ROAD. IT IS YOUR RESPONSIBILITY TO CHECK FOR THIS POSSIBILITY AND TAKE AVOIDING ACTION. FAILURE TO CHECK THIS COULD RESULT IN SERIOUS INJURY.**
- Refit pillion seat.
- Depending on local laws, attach enclosed red reflective tape in an appropriate location.
- Please test the indicators and licence plate illuminator before riding.

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 5K, Blacknest Industrial Park, Blacknest Road, Alton, Hampshire, GU34 4PX

Tel: +44 (0)870 220 6380 Fax: +44 (0)1420 521101 www.rg-racing.com Email: info@rg-racing.com